

IN THE CLAIMS

The pending claims are as follows:

1. (Previously Presented) An audio conditioning apparatus for conditioning an audio signal to be output, said audio conditioning apparatus comprising:

an input for receiving the audio signal;

5           a noise characterizing unit for determining a noise level of environmental noise;

a volume amplification unit coupled to said input for amplifying a volume of the audio signal by a volume gain in dependence on the noise level;

10           a further noise characterizing unit for determining a further noise level of the environmental noise in a bass frequency noise band or a treble frequency noise band; and

a further amplification unit coupled to said volume amplification unit for amplifying by a further gain the amplitude  
15 of frequency components in a bass frequency audio band or a treble frequency audio band of the audio signal, in dependence of the further noise level in the base or treble frequency band, respectively,

wherein said audio conditioning apparatus further comprises:

20           a gain dispatcher unit coupled to said input for allocating a maximum allowable gain of the volume amplification unit and the further amplification unit on the basis of available headroom for amplification.

2. (Previously Presented) The audio conditioning apparatus as claimed in claim 1, wherein an upper limit of the bass frequency audio band substantially lies in the range of 60 to 150 Hz, and wherein a lower limit of the treble frequency audio band

5 substantially lies in the range of 8kHz to 12 kHz.

3. (Previously Presented) The audio conditioning apparatus as claimed in claim 1, wherein said audio conditioning apparatus further comprises:

a gain consistency unit coupled to said noise  
5 characterizing unit and said further noise characterizing unit for yielding a gain consistently varying in time, according to a predetermined mathematical criterion.

4. (Cancelled).

5. (Previously Presented) The audio conditioning apparatus as claimed in claim 1, wherein the further amplification unit comprises a shelving filter.

6. (Previously Presented) The audio conditioning apparatus as claimed in claim 1, wherein said audio conditioning apparatus is connectable to a headphone loudspeaker usable for reproduction of the audio signal, and wherein said audio conditioning apparatus  
5 further comprises an active noise canceling unit for substantially

cancelling environmental noise in a cancellation band of frequencies, the environmental noise being measurable by a microphone.

7. (Previously Presented) The audio conditioning apparatus as claimed in claim 6, wherein said audio conditioning apparatus further comprises a distance measuring device for measuring a distance between the microphone and the headphone loudspeaker.

8. (Previously Presented) An audio reproduction apparatus, comprising:

- a loudspeaker for reproduction of an audio signal;
- an access to an input audio signal on which the audio

5 signal is based; and

- the audio conditioning apparatus as claimed in claim 1.

9. (Previously Presented) A method of conditioning an audio signal comprising the steps of:

- determining a noise level of environmental noise;
- amplifying a volume of the audio signal by a volume gain

5 in dependence on the noise level;

- determining a further noise level of the environmental noise in a bass frequency noise band or a treble frequency noise band; and

- 10 amplifying frequency components in a bass frequency audio band or a treble frequency audio band of the audio signal by a

further gain in dependence of the further noise level in the bass frequency noise band or the treble frequency noise band, respectively,

wherein said method further comprises the step of:

15            allocating a maximum allowable gain of said amplifying steps on the basis of available headroom for amplification.

10. (Previously Presented) A computer readable medium containing a computer program product enabling a processor to execute the method as claimed in claim 9.